

0685



PRO-GEL ADVANCED DRIVEWAY SEALER Data Sheet

DESCRIPTION: PRO-GEL is the ultimate driveway sealer. The advanced Gel formula enables the product to stay completely mixed in the container and eliminates the need for stirring. No more mess or extra work as this product applies easier, cleaner and faster! Advanced spaceage polymers provide superior durability and lasting protection for your blacktop surface. This product fills cracks up to 1/8" and seals worn surfaces. It restores beauty while protecting and preserving your valuable blacktop pavements. PRO-GEL offers the longest protective finish and is the best choice for your driveway, guaranteed.

PREPARATION: Driveways must be cleaned with Gardner™ Driveway Kleen™, spray on cleaner & degreaser before sealcoating. For oil stains, apply Driveway Kleen liberally and scrub into surface to penetrate oil spots. This step promotes proper bonding and will help prevent adhesion failures. Repair cracks and holes with Crack Stopper™ Rubberized Crack Filler & Patching products for longest lasting results.

TIPS FOR PROFESSIONAL RESULTS: Apply during the summer, in the morning hours of a clear warm day. Temperatures should be a minimum of 65°F and rising, but not above 90°F. While product can be applied during other times, these are the optimum ranges that provide superior results. Also, apply brush strokes perpendicular to the street entrance, this hides application imperfections. If possible, use pails containing the same batch code stamp on the top of the lid. Remember to mix all buckets to a uniform consistency, and when using multiple buckets, blend the end of one bucket with the beginning of the next to prevent shade variances. Do not apply if rain or heavy dew is expected within 24 hours. Allow to cure 24-36 hours before vehicle traffic.

APPLICATION: Mix well. Apply with brush/squeegee applicator. If pavement gets hotter than 85°F, mist with water to cool surface so sealer does not dry too fast. However, do not allow water to puddle. Apply sealer in thin coats, as two thinner layers adhere better than one thick one. Do not apply to steeply sloped surfaces, 20° incline or more, as this may present a slip hazard. If slope is in question, test small area first before applying to entire area. Note: newly paved surfaces must cure at least 12 months before applying sealer.

COVERAGE RATE: Coverage rates vary depending upon the condition of the existing surface. A brush and/or squeegee works best, allowing the sealer to penetrate the driveway surface. Working in a small area at a time apply thin coat, brushing away any excess as you seal. Use a cross pattern of application to insure all voids are filled and sealed. Driveway must cure approx. 2-4 hours for foot traffic and 24-48 hours for vehicle traffic. Humid or cloudy conditions may prolong curing time. Two thin coats are strongly recommended. Thick coats will result in uneven coverage, tracking and drying problems. Apply second coat perpendicular to the first, after the first coat has cured (approx. 3-6 hours) Approximate coverage for driveways in GOOD CONDITION: 400 sq. ft./5 gal. pail; AVERAGE CONDITION: 350 sq. ft./5 gal. pail.

CLEANUP: Soap & water when wet, or orange citrus cleaner when dry.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100°F. Do not reuse empty containers. Do not use in drinking water or food systems.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon, lbs.	9.5-10.0
Residue by Evaporation,	45%
Consistency	Brush or Squeegee
Cure Time (at recommended coverages) (50% relative humidity @ 70° F)	4-8 hrs. to set 24-48 hrs. to full cure depending on weather
Application Temperatures	68°-100°F
Flammability	N/A
Clean-up Tools	soap & water when wet orange citrus cleaner when dry

Approx. Shipping Weights: (Note: All approx. weights include container.)

5 gallons (18.9L)	52 lbs.	0685-GA
55 gallons (208.2L)	572 lbs.	0687-GA

CAUTION: HARMFUL OR FATAL IF SWALLOWED.

Keep Out Of Reach Of Children

For exterior use only. Contains petroleum based products. Keep away from heat, sparks and open flame. Eye, skin and respiratory irritant. In case of contact with eyes, flush with plenty of warm water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid prolonged breathing of vapor or spray mist. (NIOSH/MSHA TC 23C or equivalent). Use only with adequate ventilation. In case of irregular or stopped breathing, administer oxygen and/or give artificial respiration. Get medical attention, immediately. Contact with skin should be followed by washing with soap and water. If swallowed, do not induce vomiting. Call physician immediately. Do not use in drinking water or food systems. Seal container when not in use.

VOC - 2.2 g/l (0.018 lb/gal)

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

ASPHALT	C.A.S.# 8052-42-4
CLAY	C.A.S.# 1332-58-7
FILLERS	C.A.S.# 14808-60-7
POLYMERS	Proprietary Mixture
WATER	C.A.S.# 7732-18-5

Product is asbestos free.
Driveway Sealer Patent # 6,776,833 B2

©2005 Gardner Asphalt Corporation Manufactured by:
Gardner Asphalt Corporation P.O. Box 5449, Tampa, FL 33675

WARRANTY AND DISCLAIMER: For warranty to be valid, driveways must be cleaned prior to sealcoating with Gardner™ Driveway Kleen™, and use Crack Stopper™ repair products for all repairs. PRO-GEL is guaranteed to maintain a protective film on your driveway surface when applied according to our directions. If the product proves to be defective within stated warranty period, effective from the date of purchase, with your original retail receipt, it shall be replaced at the cost of manufacturer. Manufacturer will not be liable for areas that have ponding water, poor drainage problems, or snow removal damage. Failures due to acts of God, fire, structural defects or causes beyond our control are excluded from this guarantee and we are not responsible for labor or other costs incurred in the original or any replacement application. Except as stated above, we make no warranties or guarantees, expressed implied, and none should be inferred. For this guarantee to be valid, manufacturer products must be used for repair. This warranty is only for residential (single family) homes. Two coats must be applied. Not applicable on commercial parking lots.

See MSDS for more info



Gardner Asphalt Corp. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardnerasphalt.com