



1401

ALL PURPOSE SILICONIZED ACRYLIC LATEX CAULK Data Sheet

DYNAMITE® ALL PURPOSE CAULK

- Indoor/Outdoor
- Bonds & Seals All Surfaces
- Elastomeric
- Water clean-up
- Paintable

DYNAMITE® All Purpose Caulk is a premium acrylic latex formulation designed to be used in any areas that require sealing. Dynamite® applies fast and easily, provides for superior paintability and has outstanding adhesive qualities, making it useful for almost any repair. Dynamite® combines top acrylics and silicone to provide an airtight, weatherproof seal that remains tough and flexible far longer than the average caulk.

FEATURES:

- Formulated to exceed ASTM C-834
- Excellent paintability
- Superior adhesion
- Elastomeric qualities
- Contains rust inhibitor

DIRECTIONS: Clean all surfaces of contaminants. Apply sealant when the surface is clean and dry. Trim nozzle to desired bead size. The bead may be smoothed with a wet finger, sponge or brush. Clean up excess caulk with a damp cloth before it dries. This sealant may be painted when dry generally in 4 to 6 hours. For best results during periods of high humidity an extended curing time may be required. Do not caulk if rain or freezing conditions are anticipated within 24 hours. Not intended for marine use, surfaces submerged in water or for repair of surface defects. See the Dynamite® Architectural Specification Data Sheet for detailed product information.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Meets:	ASTM C 834
Color:	White
Odor:	Mild
Consistency:	Smooth Paste
Flash Point:	Above 212°F
Vehicle:	Acrylic Latex Polymer
Solvent:	Water
Pigments:	Calcium Carbonate and Titanium Dioxide
Dry To Touch:	30 - 60 minutes
Cure Time:	5 - 7 Days
% Solids:	81% +/- 2%
Recommended Storage Temperature:	40 F to 100 F.
Recommended Application Range:	45 F to 100 F.
Service Temperature Range:	-10 F to 150 F.
Shelf Life:	12 months

Approx. Shipping Weights: (Note: All approx. weights include container.)

12 - 5.5 Fl. Oz. Squeeze Tubes/Case: 15 lbs.

**CAUTION!: DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.**

INGREDIENTS:

Calcium Carbonate
Latex Emulsion
Butyl Benzyl Phthalate
Mineral Spirits
Ethylene Glycol
Titanium Dioxide
And other additives

CAS# 471-34-1
CAS# Proprietary
CAS# 85-68-7
CAS# 8052-41-3
CAS# 107-21-1
CAS# 13463-67-7

©2005 Gardner Asphalt Corporation
Manufactured by / Fabricado por: Gardner Asphalt Corporation
P.O. Box 5449, Tampa, FL 33675

See MSDS for more info

LIMITED LIFETIME WARRANTY:

We guarantee that if you use Dynamite Siliconized Acrylic Latex Tub 'N Tile Caulk as directed and it fails to perform as is indicated on this label, Sealant Technology will provide you with a free replacement cartridge. To obtain a replacement cartridge, send us a copy of your receipt with an explanation of the problem to the address below. This limited warranty applies to residential use only. Sealant Technology limits its warranty and liability strictly to replacement of product proven defective.

Sealant Technology, A Division of Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.sealanttechnology.com, www.gardner-gibson.com

