



3319-1-61

SLOW SET SILICONIZED ACRYLIC CAULK Data Sheet

DYNAMITE® 3300 SLOW SET

- Longer Open Time
• Interior/Exterior
• General Use

Dynamite® 3300 is a "slower drying" caulk designed to provide longer "open time" to work with product before it skins over.

Dynamite 3300 may be applied on wood, brick, concrete, plaster, masonry, metal and dry-wall. It provides a reliable seal for seams around doors, windows, baseboards and many household surfaces.

Why use Dynamite 3300?

- Good Adhesive Qualities
• Meets ASTM C-834
• Paintable When Cured
• Easy Water Clean Up

How do I apply Dynamite 3300?

- 1. Clean all surfaces of dirt, dust, old caulk, loose paint, wax, grease, oil and mildew.
2. Trim nozzle to the desired bead size and load in caulk gun.
3. Caulk may be smoothed with a wet finger, sponge or brush.
4. Use soap and water to clean up hands and tools.
5. Caulk is designed to give extended open time in hot or dry climates.
6. Do not caulk if rain or freezing conditions are anticipated within 24 hours of application.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Table with 2 columns: Property and Value. Includes rows for Meets (ASTM C 834), Color (White), Odor (Mild), Consistency (Smooth Paste), Flash Point (Not Applicable), Vehicle (Acrylic Latex), Solvent (Water), Pigments (Calcium Carbonate and Titanium Dioxide), Dry To Touch (30 - 60 minutes), Cure Time (5 - 7 Days), % Solids (80% +/- 2%), Recommended Storage Temperature (40 F to 100 F), Recommended Application Range (45 F to 100 F), Service Temperature Range (-10 F to 150 F), Flash Point (None), Shelf Life (12 months).

Approx. Shipping Weights: (Note: All approx. weights include container.)

Table with 2 columns: Quantity and Weight. Includes rows for 12 - 10.1 Fl. Oz. Tubes/Case (15 lbs.) and Cases Per Pallet (140 Cases).

CAUTION! HARMFUL IF SWALLOWED. DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.

Avoid breathing vapors, use only in a well ventilated area. Avoid contact with eyes or skin. Seek medical attention if irritation develops. DO NOT STORE OR APPLY AT TEMPERATURES BELOW 40°F.

VOC: < 54 g/L

INGREDIENTS:

Table with 2 columns: Ingredient and CAS#.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer.

LIMITED 40 YEAR GUARANTEE:

We guarantee that if you use Dynamite 3300 Siliconized Acrylic Caulk as directed and it fails within 40 years of proper application, Sealant Technology will provide you with a free replacement cartridge.

From the makers of:



Sealant Technology, A Division of Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449 Phone: (813) 248-2101 • Fax (813) 248-6768 • www.sealanttechnology.com, www.gardner-gibson.com

