



5019-1-61

SILICONIZED ACRYLIC LATEX SEALANT Data Sheet

DYNAMITE® 5000 WHITE

- Interior / Exterior Elastomeric Caulk
Multi-Purpose Use
Elastomeric

Dynamite® 5000 is a better quality siliconized acrylic latex caulk designed for general purpose sealing for interior or exterior applications.

Dynamite 5000 may be applied on wood, metal, brick, concrete, plaster, masonry, drywall, glass or tile.

Why use Dynamite 5000?

- Formulated to exceed ASTM Specification C-834
Excellent Adhesive Qualities
Interior and Exterior Durability
Great Paintability
Easy Water Clean Up
Contains Rust Inhibitors

How do I apply Dynamite 5000?

- 1. Clean all surfaces of dirt, dust, old caulk, loose paint, wax, grease, oil and mildew.
2. Trim nozzle to the desired bead size and load in caulk gun.
3. Sealant may be smoothed with a wet finger, sponge or brush.
4. Excess sealant can be cleaned up before it dries with a wet cloth.
5. This sealant can be painted over when dry, generally 4 to 6 hours.
6. Do not caulk if rain or freezing conditions are anticipated within 24 hours of application.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Table with 2 columns: Property and Value. Includes rows for Meets (ASTM C 834), Color (White), Odor (Mild), Consistency (Smooth Paste), Flash Point (Not Applicable), Vehicle (Acrylic and Latex Polymers with Silicone), Solvent (Water), Pigments (Calcium Carbonate and Titanium Dioxide), Dry To Touch (30 - 60 minutes), Cure Time (5 - 7 Days), % Solids (82% +/- 2%), Recommended Storage Temperature (40 F to 100 F), Recommended Application Range (45 F to 100 F), Service Temperature Range (-10 F to 150 F), Shelf Life (12 months).

Approx. Shipping Weights: (Note: All approx. weights include container.)

Table with 2 columns: Quantity and Weight. Includes rows for 12 - 10.1 Fl. Oz. Tubes/Case (15 lbs.) and Cases Per Pallet (140 Cases).

CAUTION! DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.

Avoid breathing vapors, use only in a well ventilated area. Avoid contact with eyes or skin. Seek medical attention if irritation develops. DO NOT STORE OR APPLY AT TEMPERATURES BELOW 40°F.

VOC: < 46 g/L

INGREDIENTS:

Table with 2 columns: Ingredient and CAS#. Includes Calcium Carbonate, Acrylic Polymer, Diisooheptyl Phthalate, Mineral Spirits, Ethylene Glycol, and Titanium Dioxide.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer.

LIMITED 45 YEAR GUARANTEE: We guarantee that if you use Dynamite 5000 Siliconized Acrylic Sealant as directed and it fails within 45 years of proper application, Sealant Technology will provide you with a free replacement cartridge.

See MSDS for more info

Sealant Technology, A Division of Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.sealanttechnology.com, www.gardner-gibson.com

