



6426

**FREEWAY BLACKTOP DRIVEWAY SEALER**  
Data Sheet

- Premium filler and sealer
- Renews blacktop surfaces
- 4x polymer concentration
- Your better quality choice

**DESCRIPTION:** **FREEWAY Blacktop Driveway Sealer** is a new, high performance formulation designed to outlast traditional products and provide easy application. Unlike most products, **FREEWAY** is a polymer modified filler sealer. These unique polymers add strength and durability and provide the best protection against gas, oil and other destructive chemicals. **FREEWAY** is also processed to allow non-skid sand particles, which fill cracks up to 1/6" wide, to remain in suspension providing faster and easier application. This product will restore a natural jet black finish and extend the life of your blacktop surface.

**PREPARATION:** Newly paved asphalt surfaces must be allowed to cure for a minimum of six months or a full summer season prior to application of any sealer. All surfaces with dirt, oil spots and gasoline soaked areas must be cleaned with driveway cleaner and primed with Driveway Essentials Oil Spot Primer. Repair cracks and holes with Crack Stopper repair products. All repaired areas must be allowed to fully cure prior to application of sealer. See individual product instructions.

**APPLICATION:** Mix thoroughly. DO NOT apply if rain is expected within 24-36 hours. DO NOT thin. Using a cross pattern of application, apply sealer in thin even coats brushing away any excess as you seal. Allow driveway to fully cure (approx. 24-48 hours) prior to allowing traffic. Shaded areas, humid or cloudy conditions may prolong curing time. DO NOT use on Concrete, Flagstone, Brick or Clay surfaces.

**CLEAN-UP:** Clean tools with water and soap immediately after use.

**COVERAGE:** A five gallon pail will cover 300-400 sq. ft. depending upon the surface. Slightly more coverage may be expected on previously sealed driveways. Immediately after use, clean tools with soap and water.

**PRECAUTIONS:** Protective clothing and eye wear should be used during application of this product. Product may cause skin irritation; proper protection is required. When transporting this product, ensure that lid is tight and pail secured and upright. Close container when not in use. DO NOT allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not store at temperatures above 110° F. Keep from freezing.

Do not apply on newly laid pavements until at least one full summer season of weathering has occurred. Best when applied in the early morning on a clear day when air and pavement temperatures are above 65° F and rising. Do not apply if heavy dew or rain is forecasted for at least 24-36 hours.

**TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS**

Weight Per Gallon	8.8-9.8 lbs.
Residue by Evaporation, %	44 min.
Combustible Solvents	None
Consistency	Brush or Squeegee
Cure Time (50% Relative Humidity, 70°F)	4-8 hours
Full Cure (50% Relative Humidity, 70°F)	24-48 hours
Application Temperatures	65°-100°F
Flammability	N/A waterbased
Clean-up Tools	Soap & water when wet Citrus solvent or mineral spirits when dry

**Approx. Shipping Weights:** (Note: All approx. weights include container.)

5 gallons (18.9L)	50 lbs.
55 gallons (208.2L)	550 lbs.

**DANGER!: HARMFUL OR FATAL IF SWALLOWED.**  
**EYE, SKIN AND RESPIRATORY IRRITANT.**

**DO NOT THIN. STIR THOROUGHLY BEFORE AND DURING USE. APPLY EARLY IN THE DAY TO GAIN MAXIMUM DRYING TIME FROM DAYTIME WARMTH. DO NOT APPLY IF HEAVY DEW OR RAIN IS EXPECTED WITHIN 48 HRS.**

**Apply when weather temperature is at least 65°F**  
If swallowed **DO NOT** induce vomiting. Call physician.

In case of :  
Eye contact - flush with plenty of warm water. Skin contact - wash thoroughly with soap and water. Irregular or stopped breathing - administer oxygen, give artificial respiration.  
Get medical attention (immediately). Avoid prolonged breathing of vapor or spray mist. (NIOSH/MSHA TC 23C or equivalent).

**Use with adequate ventilation.**  
**Keep Out of Reach of Children.**  
**VOC/VOS=0**

ASPHALT/EI Asfalto	C.A.S.# 8052-42-4
CLAY/La Arcilla	C.A.S.# 1332-58-7
FILLERS	C.A.S.# 14808-60-7
POLYMER	Proprietary/Mixture

**WARRANTY AND DISCLAIMER:**  
For limited warranty and disclaimer information, contact the Gardner-Gibson, Inc. corporate office at 1-800-237-1155 or www.gardner-gibson.com.

See MSDS for more info



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449  
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardnerasphalt.com