



7019-1-61

ELASTOMERIC ACRYLIC SEALANT
Data Sheet

DYNAMITE® 7000 WHITE

- Premium Interior / Exterior
• All Purpose
• Highly Flexible
• Ideal For Crown Moulding

Dynamite® 7000 is a premium quality elastomeric acrylic caulk designed for all purpose sealing for interior or exterior applications.

Dynamite 7000 may be applied on wood, metal, brick, concrete, plaster, masonry, drywall, glass or tile.

Why use Dynamite 7000?

- Includes Silicone
• Resists Rust Bleed-through
• Soap and Water Clean Up
• Meets ASTM C-920
• Excellent Paintability
• All Weather Durability
• Exceptional Adhesion
• Permanently Flexible

How do I apply Dynamite 7000?

- 1. Clean all surfaces of dirt, dust, old caulk, loose paint, wax, grease, oil and mildew.
2. Trim nozzle to the desired bead size and load in caulk gun.
3. Sealant may be smoothed with a wet finger, sponge or brush.
4. Excess sealant can be cleaned up before it dries with a wet cloth.
5. This sealant can be painted over when dry, generally 6 to 8 hours.
6. Do not caulk if rain or freezing conditions are anticipated within 24 hours of application.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Table with 2 columns: Property and Value. Includes rows for Exceeds, Color, Odor, Consistency, Flash Point, Vehicle, Solvent, Pigments, Dry To Touch, Cure Time, % Solids, Recommended Storage Temperature, Recommended Application Range, Service Temperature Range, and Shelf Life.

Approx. Shipping Weights: (Note: All approx. weights include container.)

Table with 2 columns: Quantity and Weight. Includes rows for 12 - 10 Fl. Oz. Tubes/Case (15 lbs.) and Cases Per Pallet (140 Cases).

CAUTION! HARMFUL IF SWALLOWED. DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.

Avoid breathing vapors, use only in a well ventilated area. Avoid contact with eyes or skin. Seek medical attention if irritation develops. DO NOT STORE OR APPLY AT TEMPERATURES BELOW 40°F.

VOC: less than 1.5% by wt.

INGREDIENTS:

Table with 2 columns: Ingredient and CAS#.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm.

LIMITED 55 YEAR GUARANTEE: We guarantee that if you use Dynamite 7000 Elastomeric Acrylic Sealant as directed and it fails within 55 years of proper application, Sealant Technology will provide you with a free replacement cartridge.

See MSDS for more info

Sealant Technology, A Division of Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.sealanttechnology.com, www.gardner-gibson.com

