

MATERIAL SAFETY DATA SHEET

NPCA

FOR COATINGS, RESINS AND RELATED MATERIALS
(Approved by US Department of Labor Essentially Similar to Form OSHA 20)

Date Issued: 12/20/05

Page 1 of 2

SECTION I – COMPANY AND PRODUCT IDENTIFICATION

MANUFACTURER'S NAME**GARDNER-GIBSON CORPORATION**STREET ADDRESS

4161 E. 7TH AVENUE

CITY, STATE, AND ZIP CODE

TAMPA, FL 33605

EMERGENCY TELEPHONE NUMBER

1-800-424-9300

PRODUCT CLASS

Acrylic Latex Sealant

MANUFACTURER'S CODE IDENTIFICATION

Dynamite 7000 – Product #7019-1-61

TRADE NAME

Dynamite 7000 Elastomeric Acrylic Sealant – White

SECTION II- COMPOSITION/ INGREDIENTS

INGREDIENT	PERCENT By Weight	TLV PPM	PEL - TWA PPM
Mineral Spirits CAS # 8052-41-3	< 1.0%	100	100
Acrylic Polymer CAS# Proprietary	> 40.0%	N.E.	N.E.

N.E. = Not Established

SECTION III – PHYSICAL DATA

BOILING RANGE: 212°F - 215°F

VAPOR DENSITY HEAVIER LIGHTER, THAN AIR

VAPOR PRESSURE: 25 mm Hg @ 68°F

EVAPORATION RATE FASTER SLOWER, THAN
ETHERPERCENT VOLATILE BY
VOLUME: 28 - 30 %WEIGHT PER GALLON:
12.1 Lbs.

SOLUBILITY IN WATER: Dispersible

PHYSICAL STATE: Paste

pH 8.5

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT- WATER BASED – Not Applicable**Explosion Hazard: Not Applicable****LEL – Not Applicable**

EXTINGUISHING MEDIA - Carbon dioxide, dry chemical, foam, or water spray

UNUSUAL FIRE AND EXPLOSION HAZARDS – None

SPECIAL FIRE FIGHTING PROCEDURES - Water can be used to cool fire-exposed containers. Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals

SECTION V - REACTIVITY DATA

STABILITY: UNSTABLE STABLECONDITIONS TO AVOID: Store away from strong
oxidizing materials.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container closed when not in use. Protect from freezing.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon oxides and traces of incompletely burned carbon compounds.

HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR

MATERIAL SAFETY DATA SHEET

Dynamite 7000 – White

Page 2 of 2

SECTION VI - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE -

ACUTE EFFECTS:

EYES: Direct contact may cause slight to moderate irritation. SKIN: May cause slight irritation to sensitive skin. INHALATION: Irritates respiratory passages very slightly. INGESTION: Low ingestion hazard in normal use.

PROLONGED/REPEATED EXPOSURE EFFECTS:

SKIN: No known applicable information. INHALATION: No known applicable information. INGESTION: None known.

EMERGENCY FIRST AID PROCEDURES –

EYES: Flush with water for 15 minutes. Get medical attention if irritation persists.
SKIN: Wash with soap and water or waterless cleanser. Get medical attention if irritation develops or persists.
INHALATION: If symptoms develop, move to fresh air.
INGESTION: Do not induce vomiting. If symptoms develop, seek medical advice from a physician.
No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Observe all personal protection equipment recommendations described in Section VIII. Wipe up or scrape up and contain for disposal. Final cleaning may require use of hot water and/or detergents. Dispose of saturated absorbent or cleaning materials appropriately.

WASTE DISPOSAL METHOD: Dispose of unused material in accordance with Federal, State, and Local Regulations.

SECTION VIII – PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use with adequate ventilation.
SKIN PROTECTION: Protective gloves are recommended for prolonged exposure.
EYE PROTECTION: Safety glasses with side shields.
OTHER PROTECTIVE EQUIPMENT: None required.

SECTION IX – TRANSPORTATION and REGULATORY INFORMATION

DOT Proper Shipping Name: Not Regulated by D.O.T. **DOT Hazard Class:** None
DOT UN/NA Number: None **Packing Group:** None

SARA Section 313: No substances are contained in this product subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of TSCA and 40 CFR part 372.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

California Proposition 65: This product contains a chemical known to the state of California to cause cancer and contains a chemical known to the state of California to cause birth defects or reproductive harm.

SECTION X – OTHER INFORMATION

OTHER PRECAUTIONS: KEEP OUT OF THE REACH OF CHILDREN. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM FREEZING.

VOC: 39 grams/Liter of material

Hazardous Materials Identification System (HMIS)

Health	Flammability	Reactivity	Personal Protection
1	0	0	C

Prepared by: M. Jones
12-20-05